


Upholstered ottoman with steel sled base available in different finishes.



Frame Sled base of 12 mm diameter steel rod. Polypropylene glides.

Seat Upholstered cushion with flexible fire resistant polyurethane foam with density between 25 kg/m³ and 40 kg/m³.

Other materials Zinc-nickel electrolyte screws. Polyvinyl acetate glue.

Accessories Polypropylene, felt or steel glides.

Leather/Cuero Leather

Leather

Grade L1
High grade cow leather (21)

Grade L3
Polished full grain leather (21)

Fabrics

Telas

Grade 1
Era (20)
Citadel (20)
Gravity (30)
Jacquard 1 (10)
Jacquard 3 (15)
Microfibra (14)
Rivet (24)
Sand (5)
Urban (24)
Xtreme (25)

Grade 2
Solid & Stripes (14)

Grade 3
Jacquard 4 (15)
Linen (8)
Main Line Flax (42)
Medley (37)
Natte (9)
Revive 1 (25)

Grade 2
High Tech One (6)
Jacquard 2 (15)

Grade 4
Cava 3 (49)
Field (24)
Floyd (23)

Grade 4
Hemp (21)
Jacquard 4 (21)
Special (15)
Nexus (15)
Oxygen (32)
Remix 2 (49)

Grade 5
Blazer (60)
Messenger 4 (44)
Silk (21)
Step (57)
Step Melange (54)
Synergy (75)

Grade 6
Chartres (13)
Ciara 2 (24)
Craggan (10)
Go Check (40)
Swing (29)

Grade 7
Canvas 2 (45)
Rime (27)

Grade 8
Harald 3 (30)
Lopi (15)
Tonus 4 (64)
Tonus Meadow (24)

Grade 8
Divina MD (27)
Divina Melange 2 (24)
Hallingdal 65 (58)
Steelcut Trio 3 (54)

Ecopiel

1 Valencia (16)
2 Silvertex (15)
4 Dolce (15)
5 Ledger (28)
7 Sudden (30)

Resistance and Quality ISO 9001:2008
UNE-EN 16139:2013

Fireproof BS 5852:1982 Part 2
California Technical Bulletin 117
UNE-EN 1021-1:2006
UNI 9175 (class 1 IM)

Sustainability ISO 14001:2004
ISO 14006:2011
level 1 ANSI/BIFMA