



High back lounge chair with upholstered seat and backrest, and a four star aluminum central swivel base, self-return system and finished in polished aluminum, white or black. Optional Tilting mechanism.



26.49



40



1

	Back height	Seat height	Arm height	Width	Depth
Measures inch.	43,25	17,00	19,00	29,50	31,50

Frame	4-star aluminum central swivel base with self-return system and finished in polished aluminum, white or black. Polished aluminum plate fixes the base to the seat. Central column is a 52 mm. aluminum tube with integrated self-return. Polypropylene glides.
Seat	Solid beech structure with polypropylene elastic straps covered with flame retardant polyurethane flexible foam with a density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood shell with flexible flame retardant foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accessories	Polypropylene, felt or steel glides.

Leather

Leather

- L1 High grade cow leather
- L3 Polished full grain leather
- L6 Aniline leather batique-effect. Scandinavian cattle.

Fabrics

Fabrics / Telas

- 1 Jacquard One
- Jacquard Three
- Sand
- Era
- Gravity
- Rivet
- Urban

- 2 Jacquard Two

- 3 Jacquard Four
- Medley
- Revive 1
- Maglia
- Main Line Flax
- Loom Two

- 4 Jacquard 4 Special
- Hemp
- Nexus
- Oxygen
- Floyd
- Remix 2
- Heritage
- Savane
- Loom Three
- Loom Four

- 5 Silk
- Synergy
- Step
- Step Melange
- Messenger 5
- Blazer
- Melange Nap
- Glow

- 6 Capture
- Fiord
- Tonus 4
- Divina 3
- Lopi

- 7 Canvas 2
- Rime

Faux Leather / Ecopiel

- 1 Valencia
- 2 Silvertex
- 4 Dolce
- 6 Ledger

- 8 Capture
- Fiord
- Tonus 4
- Divina 3
- Lopi

- 9 Divina MD
- Divina Melange 3
- Hallingdal 65
- Steelcut Trio 3

Aluminum finish



Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BKZ 5.2

BS 5852 Part 2 Crib 5

California Technical Bulletin 117

UNE-EN 1021-1 & 2

UNI 9175 (class 1 IM)

Sustainability

FSC

ISO 14001

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard