



Armchair with upholstered seat and backrest, steel sled base finished in polished chrome, white or black.



	Back height	Seat height	Arm height	Width	Depth
Measures inch.	30,50	18,00	24,00	26,50	24,50

Frame	Sled base of 12 mm diameter steel rod. Polypropylene glides.
Seat	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Back	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Arms	Beech plywood covered with flexible flame retardant polyurethane foam with density between 25 kg/m ³ and 40 kg/m ³ .
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Accessories	Polypropylene, felt or steel glides.
Leather	<p>Leather</p> <p>L1 High grade cow leather</p> <p>L3 Polished full grain leather</p> <p>L6 Aniline leather batique-effect. Scandinavian cattle.</p>

Fabrics

Fabrics / Telas

1 Jacquard One
Jacquard Three
Sand
Era
Gravity
Rivet
Urban

2 Jacquard Two

3 Jacquard Four
Medley
Revive 1
Maglia
Main Line Flax
Loom Two

4 Jacquard 4 Special
Hemp
Nexus
Oxygen
Floyd
Remix 2
Heritage
Savane
Loom Three
Loom Four

5 Silk
Synergy
Step
Step Melange
Messenger 5
Blazer
Melange Nap
Glow

6 Capture
Fiord
Tonus 4
Divina 3
Lopi

7 Canvas 2
Rime


8 Capture
Fiord
Tonus 4
Divina 3
Lopi

9 Divina MD
Divina Melange 3
Hallingdal 65
Steelcut Trio 3

Faux Leather / Ecopiel

1 Valencia
2 Silvertex
4 Dolce
6 Ledger


Aluminum finish



Polished aluminum




White



Black

Steel finish



Polished Chrome

Resistance and Quality

Indoor Air Quality-Advantage Gold

ISO 9001

UNE-EN 16139

Fireproof

BS 5852 Part 2 Crib 5

California Technical Bulletin 117

UNE-EN 1021-1 & 2

UNI 9175 (class 1 IM)

Sustainability

ISO 14001

ISO 14001

level® 2 certified to ANSI/BIFMA e3 Standard