Andreu World

BU1841 Flex Executive

Piergiorgio Cazzaniga



High back lounge chair with upholstered shell and aluminum swivel four-star base with self-return and finished in polished aluminun, white or black. Additional options include: parallel upholstery stitching, tilt mechanism and back finished in walnut veneer.



20.13 🚵 35



lh ₁

Measures	
inch	

Back height	Seat height	Width	Depth
48.25	15.75	23.25	26.00

4-star aluminum central swivel base with self-return system and finished in polished aluminum, white or black. Polypropylene glides. Optional tilting system.

Seat

Frame

Upholstered shell with flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Optional parallel stitching.

Back

Upholstered shell with flame retardant foam with density between 25 kg/m3 and 40 kg/m3. Optional parallel stitching. Optional walnut veneer back.

Other materials

Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.

Accesories

Felt glides.

Leather

- L1 High grade cow leather
- L3 Polished full grain leather
- **L6** Aniline leather batique-effect. Scandinavian cattle.

Andreu World

BU1841 Flex Executive

Piergiorgio Cazzaniga

Fabrics

Fabrics / Telas

- 1 Jacquard One Jacquard Three Sand Era Gravity Rivet Urban
- 2 Jacquard Two
- 3 Jacquard Four Medley Revive 1 Maglia Main Line Flax Loom Two
- 4 Jacquard 4 Special Hemp Nexus Oxygen Floyd Remix 2 Heritage Savane

Loom Three

Loom Four

- 5 Silk Synergy Step Step Melange Messenger 5 Blazer Melange Nap
- 6 Capture Fiord Tonus 4 Divina 3 Lopi

Glow

7 Canvas 2 Rime

8 Capture Fiord Tonus 4

Lopi 9 Divina MD Divina Melange 3 Hallingdal 65 Steelcut Trio 3

Divina 3

Faux Leather / Ecopiel

- Valencia
 Silvertex
- 4 Dolce 6 Ledger

Aluminum

finish



Aluminum finish







EPXN Black

Resistance and

Indoor Air Quality-Advantage Gold

Quality

ISO 9001

UNE-EN 16139

Fireproof

BKZ 5.2

BS 5852 Part 2 Crib 5

California Technical Bulletin 117

UNE-EN 1021-1 & 2 UNI 9175 (class 1 IM)

Sustainability

ISO 14001

ISO 14001

level® 1 certified to ANSI/BIFMA e3 Standard